

---

**HANDBOOK  
SUPPLEMENT  
JJM 10 02 14/871**

---

This supplement replaces the tyre pressure tables shown on the inside front cover of the Driver's Handbook, JJM 10 02 14/87  
and page 82 of the Vehicle Care Handbook, JJM 10 16 14/87

### **Tyre Pressures**

#### **Recommended Tyre Pressures**

Tyres recommended in SECTION 6 of the Vehicle Care Handbook must be inflated to the following cold inflation pressures:

		Maximum Comfort – Speeds up to 160 km/h (100 mph)	Normal Pressures
17 inch wheels	Front	180 kPa (1,8 kg/cm <sup>2</sup> , 1,7 bar, 26 lbf/in <sup>2</sup> )	220 kPa (2,24 kg/cm <sup>2</sup> , 2,2 bar, 32 lbf/in <sup>2</sup> )
	Rear	190 kPa (2,0 kg/cm <sup>2</sup> , 1,9 bar, 28 lbf/in <sup>2</sup> )	230 kPa (2,4 kg/cm <sup>2</sup> , 2,3 bar, 34 lbf/in <sup>2</sup> )
18 inch wheels	Front	180 kPa (1,8 kg/cm <sup>2</sup> , 1,7 bar, 26 lbf/in <sup>2</sup> )	220 kPa (2,24 kg/cm <sup>2</sup> , 2,2 bar, 32 lbf/in <sup>2</sup> )
	Rear	190 kPa (2,0 kg/cm <sup>2</sup> , 1,9 bar, 28 lbf/in <sup>2</sup> )	230 kPa (2,4 kg/cm <sup>2</sup> , 2,3 bar, 34 lbf/in <sup>2</sup> )
Temporary-use spare wheel		–	420 kPa (4,2 kg/cm <sup>2</sup> , 4,0 bar, 60 lbf/in <sup>2</sup> )

#### **Tyres without Jaguar approval**

Tyres other than those recommended must be inflated to the following cold inflation pressure (front and rear):

300 kPa (3,1 kg/cm<sup>2</sup>, 3,0 bar, 44 lbf/in<sup>2</sup>)

When using non-Jaguar approved winter tyres, inflate to the above recommended tyre pressure and do not exceed the tyre's speed capability.